



Ionization ramp 2,3 or 4 Fans Ap& T Dj2712

Ionization ramp with 2,3 or 4 fans. The ionization fan is equipped with pulsating DC technology for effective removal of static electricity. The fan has five adjustable speeds. Can be adjusted with remote control.

Article.no

2 fans	M20934
3 fans	M20935
4 fans	M20936

Dimensions

2 fans	BxDxH 500x67x154 mm
3 fans	BxDxH 750x67x154 mm
4 fans	BxDxH 1000x67x154 mm

Technical specifications

Input voltage	DC 24V?RJ45 interface?
Ozone content	? 0,05 ppm (150 mm from the air outlet)
Power consumption	33/44/55 W
Working temperature	0–50 ?
Output voltage	DC $\pm 4KV$? $\pm 7KV$
Working humidity	70% RH
Ion release	Pulsed DC
Discharge electrode	Tungsten alloy
Outer material	Aluminum with powder coating
Ion discharge area	750x550/800/1050 mm
Power supply	AC100-240V 50/60Hz
Discharge rate	? 1,5 s (150 mm in front of the air outlet)
Ion balance	-15V ? +15V (150 mm from the air outlet)
Air flow	135 x 3 CFM
Sound level	? 58 dB (1 m from the air outlet)
Weight	3,2/3,9/4,2 kg